

Polyethylene Spiral Guard



Application Protection spiral for hose and cables

Temp. range -20°C to +60°C

Part number	Hose size - 1 wire	Hose size - 2 wire	I.D	O.D	Wall Thickness	Spiral Pitch	W	L	Box Qty
			mm	mm	mm	mm	g/m	m	
PSG-10			7,5	10	1,25	9	32	20	400
PSG-12	3/16		9,5	12	1,25	11	39	20	300
PSG-16	1/4	3/16	13	16	1,5	15	64	20	150
PSG-20	5/16	1/4 + 5/16	16	20	2	18	106	20	100
PSG-25	3/8	3/8	20	25	2,5	22,5	166	20	60
PSG-29	1/2	1/2	24	29	2,5	28	196	20	50
PSG-32	5/8	5/8	27	32	2,5	30	217	10	40
PSG-35	3/4	3/4	30	35	2,5	30	239	10	30
PSG-40	1	1	35	40	2,5	28	276	10	25
PSG-50	1 1/4	1 1/4	44	50	3	28	415	2	15
PSG-60	1 1/2	1 1/2	50	60	5	28	810	2	10
PSG-70		1/2	60	70	5	32	958	2	8
PSG-75		2	65	75	5	32	1032	2	5
PSG-85			75	85	5	35	1180	5	5
PSG-90			80	90	5	35	1252	3	3
PSG-110			100	110	5	35	1548	2,5	2,5

Hydraulic Hose Steel Spiral Guard



Application Hoses that are subjected to abrasion

Material Steel / Electro galvanised, yellow chromized

Length Min 3m

Temp. range -20°C to +60°C

Part number	Hose size	I.D
	Inch	mm
HSG-04A	1/4	16,50
HSG-06A	3/8	22,00
HSG-08A	1/2	25,20
HSG-10A	5/8	29,30
HSG-12A	3/4	32,50
HSG-16A	1	40,00
HSG-20A	1 1/4	50,00
HSG-24A	1 1/2	54,20
HSG-32A	2	68,50